

Article name : DAYTONA

Description

superior soft tannage combined with a two tone effect that resembles the natural features of an aniline leather

Technical data

Finish type : Protected
Size : 40 sq ft
Thickness : 1.1 – 1.2 mm
Color : 3

Testing

TEST	METHOD	RESULT
BALLY FLEX	ISO 5402	≥60000
FASTNESS TO CROCKING	ISO 11640	
	DRY	500 CYCLES
	WET	250 CYCLES
FINISH ADHESION(N/CM DRY)	ISO 11644	≥2.50
TEAR STRENGTH AND SINGLE EDGE	ISO 3377-2	≥20
XENON LIGHT FASTNESS	ISO 105 B02	≥5 BLUE WOOL
PH& PH	ISO 4045	MINPH=3.2,MAX ↑PH ≤0.7
MICROBIOLOGICAL TESTING	AATCC 30:2004	PASS
90 DAY TROPICAL CHAMBER FUNGICIDE		
SCOTCH TAPE ADHESION		MINIMAL REMOVAL OF FINISH



380 6th cross 1st floor, Wilson garden , Bangalore 560027, India
Mob:6364019955 Email : info@attarreliving.com
Facebook : Attrarre Instagram : @attrarreliving
www.attrarreliving.com